


## PYRAMID PANELS | ACCENT SERIES



### TECHLITE® Pyramid Panels

TECHLITE® Pyramid Panels provide maximum sound absorption for a wide range of applications. Available in a variety of thicknesses to suit your application, the pyramid geometry provides exceptional performance and visual interest. The TECHLITE® foam used to manufacture TECHLITE® Pyramid Panels also has advantages such as being lightweight, easy to install, and providing comprehensive sound absorption, even at very high frequencies.

### BENEFITS

- Absorbs and reduces noise
- Very low-density / lightweight
- Excellent thermal properties
- Class A fire-rated (ASTM E 84)
- Easy to install

### USES AND APPLICATIONS

- Recording studios
- Modern offices
- Gymnasiums
- Restaurants
- Industrial spaces

### PHYSICAL PROPERTIES

Material	TECHLITE® Flexible Open-Cell Melamine Foam
Service Temp	-40°F to 350°F
Density	Light Grey 0.56 ± 0.09 lb/ft <sup>3</sup> White 0.47 ± 0.13 lb/ft <sup>3</sup>
Fire Rating	Class A per ASTM E 84
Finish	White or Light Grey

### SIZES/COLORS

24" x 24" panel with thicknesses of 2", 3" and 4"  
 Natural White and Light Grey  
 Other Color Options Available

Sound Absorption Coefficient [Sabins / ft <sup>2</sup> ]										
Finish	Thickness [in]	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	SAA	NRC	Mounting Type
White	2.00	0.05	0.19	0.66	0.90	1.01	1.08	0.69	0.70	A
	3.00	0.12	0.37	0.90	1.05	1.12	1.16	0.86	0.85	A
	4.00	0.24	0.50	1.06	1.15	1.21	1.19	0.98	1.00	A
Light Grey	2.00	0.08	0.22	0.68	0.88	1.00	1.05	0.70	0.70	A
	3.00	0.15	0.36	0.91	1.05	1.12	1.15	0.85	0.85	A
	4.00	0.24	0.52	1.07	1.19	1.22	1.20	0.99	1.00	A

*Absorption results tested in accordance to ASTM C 423-09a*